



## SURFACE PRIMER INFORMATION

### Clear water base primer for use on porous surfaces

A single component water based acrylic coating used to penetrate and prime concrete, masonry surfaces and most types of porous surfaces to promote adhesion of tapes & pads.

**USAGE:** To prime porous surfaces before applying tapes & pads

**CONTAINER SIZES:** 500mls, 1 Litre, 2 Litres & 5 Litres

**COLOUR:** Clear liquid

#### **SUBSTRATE PREPARATION:**

All surfaces to be clean and sound and free of efflorescence and contamination.

Apply when temperature is above 8 degrees and the substrate is not more than slightly dry.

**APPLICATION:** To a clean surface roll or brush apply. Rough and porous surfaces will need a second coat

**DRY TIME:** 20 - 30 minutes pending upon temperature

**COVERAGE:** 8 – 10 Square metres

125mls for 18M x 50mm roll of anti-slip grip tape

10mls for 300mm x 300mm Tactile pad

20mls for 300mm x 600mm Tactile pad

**STORAGE:** Keep sealed containers in a dry place. Keep away from sunlight

**TOXICITY:** Non Toxic

**SOLVENT RESISTANCE:** Non Resistant

**WEATHER RESISTANCE:** Good

**SHELF LIFE:** 2 Years

**SAFETY DIRECTIONS:** Avoid contact with skin, eyes & clothing

#### **FIRST AID**

**EYE CONTACT:** Flush with plenty of water for at least 15 minutes. Get medical attention if irritation persists

**SKIN CONTACT:** Immediately wash skin with soap and plenty of water